


TC Mesa is the panel of choice for use as exterior walls, interior partitions, and ceilings in applications where energy efficiency is paramount. Ideal for the construction of temperature-controlled, industrial, and commercial buildings, TC Mesa is used in the distribution, processing, manufacturing, pharmaceutical, automotive, and aviation markets.

Trust TrueCore's Mesa, produced using veteran knowledge and experience for the industry's best contractors.



PANEL PROFILE AND CROSS SECTION



EXTERIOR AND INTERIOR PROFILE & TEXTURE	Mesa profile with non-directional stucco embossing or smooth surface texture
EXTERIOR FACINGS	26, 24, 22 Ga. G-90 galvanized or AZ50 aluminum coated steel
INTERIOR FACINGS	26, 24, 22 Ga. G-90 galvanized or AZ50 aluminum coated steel 26, 24 Ga. 304L and 316L stainless steel with 2B finish
EXTERIOR COATINGS	Siliconized Polyester (SMP) Fluoropolymer (PVDF) Flurothane* II, IV, V
INTERIOR COATINGS	Polyester Siliconized Polyester (SMP) Fluoropolymer (PVDF) Flurothane* II, IV, V PVC Plastisol
WIDTH	44", 40", 36"
LENGTH	8'-0" to 53'-0" standard Contact TrueCore for information and pricing on longer lengths.
THICKNESS	2", 2.5", 3", 4", 5", 6", 8"
CORE	Foamed-in-place Class 1 rated polyisocyanurate
JOINT	Double Tongue and Groove for concealed fastening
R-VALUE	R-8 per inch of thickness (nominal)

*Flurothane is a registered trademark of The Sherwin-Williams Company